

Vomat GmbH

Herlasgrüner Str. 99, D-08233 Treuen
 Telefon: 03 74 68 - 67 80 (0) Fax: (10)
 E-Mail: info@vomat.de



VOMAT GmbH, Herlasgrüner Str. 99, D-08233 Treuen

JOB PROFILE FOR FILTER SYSTEM

CUSTOMER :	project:	date :
machine(s)		
outlet height [mm]		Nominal width , middle of the outlet, sketch
machine supply pump(s) [l/min ; bar; kw]		
notes		ms pump: Kde or Vomat; pump on filter, lift pump, other pumps
material(s)		
chip shape		
amount of waste [kg/h; mg/l or l/h]		
layers/day		
disposal sack/sedimentator		
additional prefilter		
notes		
type of cooling lubricant		
current quantity of c.l. complete [l]		
c. l. in the system [l]		
viscosity cSt/ °C		
working temperature – max.		
ambient temperature		
external liquefier		
Δ temp. k/h		high accuracy, bypass
notes		
additional tank?		Zirkulation
connection electricity/air		seperate interface to the filter
floor plan	pto	
special colour		
e-mail		
method of payment / maturity		
delivery deadline/-condition		
spare parts pack / servicing		

Vomat GmbH

Herlasgrüner Str. 99, D-08233 Treuen
Telefon: 03 74 68 - 67 80 (0) Fax: (10)
E-Mail: info@vomat.de

VOMAT
FEINSTFILTERSYSTEME

SUGGESTION / MEASURES	
----------------------------------	--

1 m

A large grid for technical drawing, consisting of 14 columns and 20 rows of squares. A vertical dimension line on the left side of the grid indicates a height of 1 meter. A horizontal dimension line above the first row of the grid indicates a width of 1 meter.

Vomat GmbH

Herlasgrüner Str. 99, D-08233 Treuen
Telefon: 03 74 68 - 67 80 (0) Fax: (10)
E-Mail: info@vomat.de

